




引導式對邊法蘭滾珠直線軸承-LMTP



LMTP6~13



LMTP16~30

主要尺寸															法蘭垂 直度	偏心 (max.)	基本額定荷重			
型號	鋼珠列	重量 g	內徑		外徑		長度		ℓ	法蘭				聯接孔			動 C(kgf)	靜 Co(kgf)		
			dr	公差	D	公差	L	公差		Df	W	t	A	F					d1	d2
LMTP 6	4	21	6	0	12	0	19	± 0.30	5	28	18	5	20	3.5	6	3.1	0.012	0.012	21	27
LMTP 8		33	8		15	-0.013	24		32	21	6	24	52						41	
LMTP10		64	10		19	29	40		25	6	29	38	56							
LMTP12		68	12		-0.009	21	0		30	42	27	32	42						61	
LMTP13		81	13		-0.016	23	0		32	43	29	33	52						79	
LMTP16		112	16		28	37	-0.20		48	34	6	31	22						79	120
LMTP20	167	20	32	42	54	38	8	36	24	88	140									
LMTP25	6	325	25	0	40	0	59	0	8	62	46	8	40	32	5.5	9	5.1	100	160	
LMTP30		388	30	-0.010	45	-0.019	64	-0.30	10	74	51	10	49	35	6.6	11	6.1	160	280	